

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventorship ..... Feinleib et al.  
Applicant ..... Microsoft Corporation  
Attorney's Docket No. .... MS1-288US  
Title: System and Method for Synchronizing Streaming Content with Enhancing Content Using Pre-  
announced Triggers

TRANSMITTAL LETTER AND CERTIFICATE OF MAILING

To: Commissioner of Patents and Trademarks      From: Lewis C. Lee (509) 324-9256  
Washington, D.C. 20231      Lee & Hayes, PLLC  
W. 201 North River Drive, Suite 430  
Spokane, WA 99201


The following enumerated items accompany this transmittal letter and are being submitted for the matter identified in the above caption.

1. Transmittal Letter with Certificate of Mailing included.
2. PTO Return Postcard Receipt
3. New patent application (title page plus 38 pages, including claims 1-43 & Abstract)
4. Executed Declaration
5. 5 sheets of formal drawings (Figs. 1-5)
6. Assignment w/Recordation Cover Sheet

Large Entity Status ☒      Small Entity Status ☐

The Commissioner is hereby authorized to charge payment of fees or credit overpayments to Deposit Account No. 50-0463 in connection with any patent application filing fees under 37 CFR 1.16, and any processing fees under 37 CFR 1.17.

Date: March 31, 1999


By:   
Lewis C. Lee  
Reg. No. 34,656

CERTIFICATE OF MAILING

I hereby certify that the items listed above as enclosed are being deposited with the U.S. Postal Service as either first class mail, or Express Mail if the blank for Express Mail No. is completed below, in an envelope addressed to The Commissioner of Patents and Trademarks, Washington, D.C. 20231, on the below-indicated date. Any Express Mail No. has also been marked on the listed items.

Express Mail No. (if applicable) EL209425205

Date: March 31, 1999

By:   
Helen M. Hare

CALCULATION OF TOTAL FEES DUE				MS1-288US		
CLAIMS FEES	Number Filed (Col. 1)	No. Extra (Col. 2)	Small Entity		Large Entity	
			Rate (\$)	Fee (\$)	Rate (\$)	Fee (\$)
Basic Fee				395		760
Total Claims	43 - 20 =	23	x 9 =		x 18 =	414
Indep. Claims	9 - 3 =	6	x 39 =		x 78 =	468
TOTAL APPLICATION FEES						
[						
Any Other Fees						
TOTAL FEES SUBMITTED						\$1,642

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICATION FOR LETTERS PATENT

**System and Method for Synchronizing Streaming  
Content with Enhancing Content Using Pre-announced  
Triggers**

Inventor(s):

David Feinleib  
Isaac A. Sheldon

ATTORNEY'S DOCKET NO. MS1-288US

1 **TECHNICAL FIELD**

2 This invention relates to a system and method for synchronizing streaming  
3 content with enhancing content. More particularly, this invention relates to a  
4 system that announces transmission of upcoming enhancing content that is to be  
5 associated with the streaming content, such as video or a television signal. The  
6 system further encompasses timely reception of the enhancing content and  
7 displaying it in conjunction with the streaming content through use of triggers.  
8

9 **BACKGROUND**

10 Video content programs, such as TV shows and pay-per-view movies, are  
11 delivered to a viewer as a continuous data stream. Programs are most commonly  
12 distributed using a wireless broadcast system or a cable system. In the first  
13 instance, the programs are broadcast over a wireless network and received at  
14 individual homes through an antenna or satellite dish. In the latter case, the  
15 programs are transmitted over cable to set-top boxes resident in the viewers'  
16 homes.

17 In traditional broadcast distribution systems, there is no opportunity for  
18 interactive control of the content by the viewer. The viewer simply has an option  
19 to watch the program, change to a different program, or turn off the television.  
20 However, as consumers have learned from playing video games on their  
21 televisions, non-interactive viewing is not nearly as fun or sensory rich as  
22 interactive entertainment.

23 To enhance the traditional way of viewing television, there has been some  
24 effort toward the production of interactive programming content. As presently  
25 contemplated, additional interactive content is created to enhance the existing

1 traditional program. This supplemental content is played along with the  
2 continuous video stream to enable viewers to interact with the program in a more  
3 involved manner than simply watching it. The supplemental content might, for  
4 example, ask the viewer questions about the episode, or play games with the  
5 viewer that relate to the show, or describe behind-the-scenes aspects of making the  
6 program, or provide links to stores that sell merchandise sponsored by the show.  
7 In addition, the content may not be tied to a particular program, but instead be used  
8 to convey general information, such as tickers for news headlines, weather  
9 information, sports scores, and so forth.

10 The Internet is rapidly emerging as a means for supplying interactive  
11 content. Resources available on the Internet are most commonly presented as  
12 HTML (hypertext markup language) pages. Users can browser through pages of  
13 information via the World Wide Web ("Web") and receive multimedia-like  
14 experiences with video, audio, images, text, and other multimedia rich resources.  
15 Newer technologies are combining the television and Internet experiences to  
16 provide interactive content. Set-top boxes, for example, are being configured to  
17 support Web browsers that enable access to Web content in addition to receiving  
18 traditional television signals. As an example, WebTV Networks, Inc.  
19 manufactures and sells a browser-based set-top box (STB) having a television  
20 tuner, a browser, and a standard network interface device that enables  
21 simultaneously viewing of both television programs and web programming.

22 Newer generations of personal computers (PCs) are being implemented  
23 with broadcast reception capabilities, allowing them to receive and display  
24 television signals. Such PCs are equipped with a television tuner and software for  
25 television reception. A Windows-brand operating system from Microsoft

1 Corporation, for example, includes software that supports a number of interactive  
2 services and reception of broadcast data and content feeds.

3 These newer interactive television technologies combine the power of  
4 traditional television with the compelling interactivity of the Internet. One  
5 common approach today is to provide the enhancing content via the vertical  
6 blanking interval (VBI) of the streaming television content. The VBI is a non-  
7 viewable portion of the television signal. In the future, enhancing content may  
8 also be provided over satellites (e.g., DVB, DSS, etc.) and as part of digital  
9 television (DTV) feeds.

10 Unfortunately, there remains a significant hurdle concerning creation and  
11 distribution of interactive programs. TV programs are typically broadcast as a  
12 continuous data stream. Attempting to synchronize the enhancing content,  
13 regardless of how that content is delivered (i.e., via the VBI, satellite feeds, etc.),  
14 with the streaming content poses a difficult design challenge.

15 The inventors have developed a system and method that address this  
16 challenge.

## 17 **SUMMARY**

18 This invention concerns a client-server architecture that synchronizes  
19 streaming content with enhancing content via pre-announced triggers.

20 According to one implementation, the architecture includes server-side  
21 components that form announcements containing information specifying how and  
22 when to receive upcoming triggers. The announcements contain such information  
23 as an identification of the sender, a broadcast locator (e.g., URL, channel,  
24 frequency, etc.) at which the triggers and enhancing data files are to be broadcast  
25

1 or multicast, a time when the triggers and data files are to be sent, and a protocol  
2 used to transmit the triggers and data files. The server transmits the  
3 announcements to a general broadcast or multicast IP (Internet Protocol) address.

4 Client-side components include a listener to monitor the IP address for the  
5 announcements and a filter to extract selected ones of the announcements.  
6 Selected announcements are stored in an electronic programming guide (EPG)  
7 database in correlation with the streaming content programs to indicate that the  
8 associated programs are interactive.

9 When a user tunes to an interactive program, the client opens a container  
10 HTML page that contains controls to receive the streaming content program and to  
11 extract the announcements from the guide database. One of the controls monitors  
12 an IP address at particular times specified by a selected announcement to receive  
13 the triggers corresponding to the interactive program.

14 The server delivers the triggers at times synchronized to the streaming  
15 content. When triggers arrive, a client control processes the triggers to coordinate  
16 presentation of the enhancing content with the streaming content. This processing  
17 may involve invoking one or more scripts in the container page or performing  
18 general navigation in the container page.

19 The client-server architecture also enables delivery of headlines and other  
20 data items employed in a ticker using pre-announced and timely broadcast triggers.  
21 The data items are carried by the triggers and accumulated into an array. The  
22 container page inserts the array into a displayed ticker.

## **BRIEF DESCRIPTION OF THE DRAWINGS**

Fig. 1 is a diagrammatic illustration of a client-server architecture for synchronizing streaming content with enhancing content using pre-announced triggers.

Fig. 2 is a block diagram of an exemplary client computing unit.

Fig. 3 shows an exemplary configuration of a client software architecture implemented on the client computing unit.

Fig. 4 shows a flow diagram showing steps in a method for synchronizing streaming content with enhancing content through use of announcements and triggers.

Fig. 5 shows an exemplary HTML page that combines streaming content with enhancing content. It also illustrates use of triggers to carry content for tickers.

## **DETAILED DESCRIPTION**

This invention concerns an architecture for synchronizing streaming content with enhancing content. The architecture governs announcement of upcoming enhancing content, reception of the enhancing content when it arrives, and association of the enhancing content with the streaming content using triggers

The enhancing content consists of a set of data files and triggers that are multicast to a pre-defined network address to cause specific actions or events to occur on any listening client. The triggers are tied to the associated streaming content. The enhancing content can take many forms, including text, images, animated images, audio, hyperlinks, controls, executable code, and so forth.



1 Announcements are sent ahead of the triggers to announce when the triggers will  
2 be broadcast and on what multicast address.

3 Another aspect of this invention concerns a way to receive headlines and  
4 other data items as triggers and accumulate them into a ticker.

### 5 6 **General Architecture**

7 Fig. 1 shows an architecture 20 that enables delivery of streaming content  
8 and enhancing content from one or more content providers, as represented by a  
9 primary content provider 22(1) and a secondary content provider 22(2), to multiple  
10 clients 24(1), 24(2), 24(3), and 24(4). The Fig. 1 illustration shows many different  
11 ways to deliver streaming and enhancing content. One way is for the same  
12 provider to deliver both forms of content directly to the clients over the same  
13 distribution network. This situation is represented by content provider 22(1)  
14 serving streaming and enhancing content over network 26 to clients 24(1) and  
15 24(2).

16 Another way is for different providers to deliver the contents separately  
17 over the same or different networks. This situation is represented by the primary  
18 content provider 22(1) serving streaming content over network 26 to clients 24(1)  
19 and 24(2) and the secondary content provider 22(2) serving enhancing content  
20 over network 28 to the clients 24(1) and 24(2).

21 Still another way is for a content provider to deliver its content to an  
22 intermediary broadcast center, which broadcasts the content to clients. This third  
23 approach is represented by either content provider 22(1) or 22(2) delivering  
24 packets to a broadcast center 30, which converts network data packets to broadcast  
25

1 packets and broadcasts the packets over a broadcast medium 32 to clients 24(3)  
2 and 24(4).

3 The networks 26, 28, and 32 represent many diverse types of networks  
4 ranging from data networks (e.g., Internet, LAN (local area network), WAN (wide  
5 area network), etc.) to television networks (e.g., cable, satellite, RF, microwave,  
6 etc.). Technologies used to implement the networks are well known and include  
7 such technologies as wire-based technologies (e.g., fiber optic, cable, wire, etc.),  
8 wireless technologies (e.g., satellite, RF, etc.), and switching technologies (e.g.,  
9 ATM (Asynchronous Transfer Mode), Ethernet, etc.). These technologies employ  
10 different data communication protocols (e.g., TCP/IP, IPX/SPX, DSS, NABTS,  
11 etc.). One specific implementation involves IP over any one of these protocols  
12 (e.g., IP/NABTS, IP/DSS, IP/DVB, etc.). For an example of IP/NABTS, please  
13 refer to co-pending US Patent Application Serial Number 08/726,529, entitled  
14 "Method for Sending Computer Network Data As Part Of Vertical Blanking  
15 Interval", which was filed October 7, 1996.

16 The primary content provider 22(1) has a streaming content server 34 to  
17 serve streaming content (e.g., video and audio) to the clients. The content may be  
18 in many different forms, such as TV programs, movies, animation, music, news,  
19 documentaries, educational productions, and the like. As an exemplary  
20 implementation, the streaming content server 34 may be implemented as personal  
21 computers or workstations running a multitasking, disk-based operating system,  
22 such as Windows NT from Microsoft Corporation, that are configured as  
23 continuous media file servers that serve data files at a constant data rate. As an  
24 alternative to a content server, the primary content provider may be a broadcast  
25 headend that broadcasts the primary content (e.g., broadcast or satellite TV).

1 The primary content provider 22(1) has an enhancing content server 36 to  
2 serve supplemental or enhancing content to the clients in order to enhance the  
3 streaming content served by the streaming content server 34. The enhancing  
4 content could alternatively be stored with the primary content and served before,  
5 along with, or after the primary content. For instance, a single server may serve  
6 both the primary and enhancing content and record the content onto a storage  
7 medium for later transmission.

8 The enhancing content may be text, graphics, video, pictures, sound, or  
9 other multimedia types, as well as applications or other executable code.  
10 Examples of enhancing content include trivia questions or games related to the  
11 program, advertisements, merchandise or other memorabilia, hyperlinks to similar  
12 programs of similar type or starring the same actor/actress, and so on.

13 In the implementation described herein, the enhancing content is  
14 constructed as a hypertext file, or more particularly as an HTML document (or  
15 "Web page") which can be rendered by a browser. The HTML document may  
16 include links to other target resources that supply even more content. In concept,  
17 the target resource can be virtually any type of object—including executable  
18 programs, text or multimedia documents, sound clips, audio segments, still images,  
19 computers, directories, and other hyperlinks. In most Web pages, hyperlink targets  
20 are files that reside on computers connected to the Internet. However, a hyperlink  
21 target can also be a particular location within a document, including the document  
22 that is currently being rendered, as well as to other files that may be locally stored  
23 at the client.

24 The primary content provider 22(1) also implements an announcement  
25 generator 38 that generates and transmits announcements to notify clients of

1 upcoming transmission of enhancing content. Through the announcements, the  
2 providers tell the clients what data will be served over the network at a given time  
3 and how to find that data.

4 The secondary content provider 22(2) is similar to the primary content  
5 provider 22(1) in that it implements an enhancing content server 40 and an  
6 announcement generator 42. These components function essentially as described  
7 above with respect to the primary content provider 22(1).

### 8 9 **Enhancing Content Stream**

10 The content providers serve both streaming content and enhancing content  
11 to the clients. The architecture employs three elements to implement reception and  
12 display of enhancing content: announcements, triggers, and data files. The first  
13 element is an “announcement” that describes the IP address and port on which  
14 corresponding triggers will be sent for a particular enhancement. The second  
15 element is a “trigger”, which tells the client to perform particular actions (e.g.,  
16 execute a script). The third element is the “data files”, which are either packages  
17 containing interactive content files or the interactive content files themselves.  
18 Together, these elements form the enhancement stream that is delivered to the  
19 client.

20 Announcements, triggers, and data files are all sent on separate IP  
21 addresses/ports. Sending an enhancement stream involves transmitting the  
22 following elements:

- 23
- 24 1. An announcement indicating a trigger address and port.
- 25 2. A special trigger indicating an address and port for file transmission.

- 1 3. A data file containing interactive content files or individual files.
- 2 4. If necessary, a trigger causing the interactive content to be extracted
- 3 out of a container file.
- 4 5. A trigger to cause the interactive content to be displayed.
- 5

6 "Announcements" inform the client that the streaming content, such as a  
7 television show, is interactive. The announcements provide details about the  
8 enhancements, the show that the content enhances, and the page that contains the  
9 enhancement's starting point. More particularly, the announcements include  
10 transmission-related information, such as an identification of the sender, a locator  
11 (e.g., URL, channel, frequency, etc.) at which the triggers and data files are to be  
12 transmitted, a time when the triggers and data files are to be sent, and a protocol  
13 used to transmit the triggers and data files. The announcements might further  
14 include information pertaining to the content of the transmission, such as a title, a  
15 type of content (e.g., sports, science fiction, mystery, action, documentary, audio,  
16 graphical, etc.), a subject matter description, a length of transmission, a rating,  
17 actor/actress names, and so forth.

18 Announcements are based on the Internet standard Session Description  
19 Protocol (SDP). An announcement is made up simply of lines of text, with  
20 identifiers on the left of an equal sign and associated text on the right. An  
21 announcement can be stored as a text file until it is ready to be broadcast.

22 There are several types of enhancement announcements. The most  
23 common types are current announcements, which refer to a show that is currently  
24 on, and channel announcements, which refer to a given channel. Table 1 illustrates  
25 a sample announcement.

**Table 1**

<b><u>Example</u></b>	<b><u>Description</u></b>
v=0	SDP Version number, must be 0.
o=enhID 2 1 IN IP4 155.55.55.55	“enhID” specifies a user identifier. “2” is the session identifier. “1” is the version identifier. “155.55.55.55” is replaced with the IP address of the server transmitting or encoding the content. As a whole this field serves as an identifier for an enhancement.
s=Title	Contains the title for the enhancement.
c=IN IP4 233.17.43.44/3	Indicates the IP address on which triggers will be sent.
t=2208988801 2208990601	Start and finish time for an enhancement.
a=EnhID:{9E2E8B20-083E-11d1-898F-00C04FBBDEBC}	Identifies the announcement as an enhancement announcement (as opposed to some other type of announcement).
m=data 17832 udp 0	Specifies the port used for sending triggers.

“Triggers” are notifications that are sent to clients at specific times during an interactive data stream. Triggers cause an action to occur on a client, such as causing a script to be executed. In this manner, the enhancing content invoked by the triggers is synchronized with the streaming content.

Each type of trigger has a different format. However, all triggers are formatted as strings containing three parts: a key or numerical identifier, the

trigger data, and a checksum value. The key is separated from the data by white space, typically a space or tab character. The format of a trigger is as follows:

Key TriggerData[checksum]

where “Key” is the numerical identifier, “TriggerData” is the trigger data, and “checksum” is the checksum value. For example, the following string might be transmitted to the client for a navigation or “Nav” trigger:

"2 bpc://MSNBC/default.htm[BA7E] "

The preceding example illustrates the syntax of the Nav trigger as it is transmitted to a client. This is not the format typically used in writing stream language files. The syntax transmitted to clients contains additional information that you do not need to specify, namely a checksum value and a fully specified Broadcast Architecture URL. The Broadcast Architecture supports several basic types of triggers as shown in Table 2.

**Table 2**

<b><u>Key</u></b>	<b><u>Name</u></b>	<b><u>Description</u></b>
0	Error	No action is taken.
1	Data	Receives data using the specified transfer protocol.
2	Nav	Displays a page. If a target is specified, for example by using a FRAME or DIV tag set, the page is displayed in that target.
3	Nav	Displays a page. This key value has the same functionality as the previous trigger and has been kept for compatibility with earlier versions.
4	Script	Runs the specified script.
6 – 999	Reserved	Reserved for future use.
1,000 and up	UserTrigger	Sends a user-defined trigger event.

Table 3 lists exemplary triggers for the navigation-type, script-type, and data-type triggers specified by the Broadcast Architecture.



**Table 3**

<b><u>Trigger Type</u></b>	<b><u>Description</u></b>	<b><u>Format</u></b>
<i>Navigation</i>		
Top Page Navigation	"Home page" for enhancements	"2 <bpc://MyEnhancement/toppage.htm>"
Target Navigation	To navigate to a named target	"2 <itv.htm>[targ:LOGO_FRAME]"
<i>Script</i>	Execute	"4 alert('Hi!');"
	ECMAScript (Jscript) in the top page	"4 Navigate('VIEW_FRAME', 'http://www.microsoft.com');"
<i>Data</i>		
FTS	Starts listening for FTS data	"1 <FTS> 233.17.43.44:2000&MyEnhancement"
CAB	Unpacks cabinet (CAB) file	"1 <CAB> bpc://MyEnhancement/toppage.cab"

Enhancement data files and their dependencies are transmitted to clients using a transfer service. One exemplary service is the File Transfer Service (FTS), which is a component of NetShow, a Microsoft product used for streaming video and data on the Internet and on Intranets using IP Multicast. FTS sends files using a transfer mechanism based on IP multicast that includes forward error correction (FEC). However, other file transfer services might be employed as well. The architecture allows use of different file transfer services as needed.

Enhancement pages, like Web pages, are typically composed of several files. For example, the enhancement file "MyEnh.htm" might contain graphic images in Graphics Interchange Format (GIF) and Joint Photographic Experts Group format (JPEG), ActiveX controls, FutureSplash animations, and other such

1 files that must be downloaded for the enhancement page to display properly.  
2 These additional files are referred to as "dependency file" or "dependencies" of the  
3 enhancement file.

4 The enhancement dependency files are stored on the client before the  
5 enhancement is displayed. Otherwise, the user may end up viewing an incomplete  
6 enhancement and will perceive the content as broken. There are several ways of  
7 handling dependencies. One approach is to allocated broadcast bandwidth and  
8 repeatedly download the dependency files. Another approach is to require the user  
9 to explicitly download the dependency files, either from a Web site or a portable  
10 medium.

11 Still another approach is to package the enhancement and all its  
12 dependencies together in a single file. In one implementation, this involves use of  
13 cabinet (CAB) files. Packing the enhancement files together with its dependencies  
14 ensures that the user receives a complete all-or-nothing viewing experience  
15 because they either get it all or nothing, which may be better than getting bits and  
16 pieces.

### 17 18 **Client System**

19 Clients 24(1)-24(4) can be implemented in a number of ways, including  
20 computers that are broadcast enabled, set-top boxes, and computer enhanced  
21 television units.

22 Fig. 2 shows an exemplary configuration of a client 24(1) implemented as a  
23 broadcast-enabled computer. It includes a central processing unit 50 having a  
24 processor 52, volatile memory 54 (e.g., RAM), and program memory 56 (e.g.,  
25 ROM, disk drive, floppy disk drive, CD-ROM, etc.). The client 24 (1) has one or

more input devices 58 (e.g., keyboard, mouse, etc.), a computer display 60 (e.g., VGA, SVGA) to display the video content and enhancing content, and a stereo I/O 62 for interfacing with a stereo system to play audio content.

The client 24(1) includes a digital broadcast receiver 64 (e.g., satellite dish receiver, RF receiver, microwave receiver, network connection, etc.) and a tuner 66 which tunes to frequencies of a broadcast network. The tuner 66 is configured to receive digital broadcast data in a particularized format, such as MPEG-encoded digital video and audio data, as well as digital data in many different forms, including software programs and programming information in the form of data files. The client 24(1) also has a modem 68 that provides access to the Internet or other network. For other implementations, the modem 68 might be replaced by a network card, an RF receiver, or other type of port/receiver.

One example implementation of a broadcast-enabled PC is described in a co-pending U.S. Patent Application Serial No. 08/503,055, entitled "Broadcast-Enabled Personal Computer," filed January 29, 1996 in the names of Gabe L. Newell, Dan Newell, Steven J. Fluegel, David S. Byrne, Whitney McCleary, James O. Robarts, Brian K. Moran; William B. McCormick, T.K. Backman, Kenneth J. Birdwell, Joseph S. Robinson, Alonzo Garipey, Marc W. Whitman, and Larry Brader. This application is assigned to Microsoft Corporation, and is incorporated herein by reference.

The client 24(1) runs an operating system 70 that supports multiple applications. The operating system is preferably a multitasking operating system that allows simultaneous execution of multiple applications. One preferred operating system is a Windows brand operating system sold by Microsoft Corporation, such as Windows 98, Windows CE, or Windows NT or other

derivative versions of Windows. It is noted, however, that other operating systems may be employed, such as the Macintosh operating system from Apple Computer, Inc. and the OS/2 operating system from IBM.

The client 24(1) further runs a Web browser 72 that is capable of navigating hyperlinks and receiving and rendering hypermedia content, such as HTML pages. As an alternative to a browser, the client may run a piece of software known as "WebTV for Windows", which is available from Microsoft Corporation.

In addition to the operating system 70 and browser 72, the client 24(1) is illustrated with a number of software programs or modules that can be started or called to receive and play enhancing content in conjunction with streaming content. The modules include an announcement listener 74, one or more filters 76, one or more controls 78, and one or more scripts 80. Listener 74 is a specialized control that operates on information provided by announcements to receive and process triggers. Each program is stored in program memory 56, loaded into volatile memory 54 when launched, and executed on the processor 52. These software components are described below in more detail with reference to Fig. 3.

The client 24(1) also has maintains a TV system services (TSS) database 82 that holds an electronic program guide (EPG) and a spool directory 84 that functions as a cache for the TV based services and to hold the enhancing data files.

### **Client Software Architecture**

Fig. 3 shows an exemplary configuration of the client software architecture 90. The streaming and enhancing content may arrive at the client in one of two ways. First, a single source (e.g., primary content provider 22(1)) may transmit both the streaming content and the enhancing content in a composite data stream.

1 In traditional television broadcast, the enhancing content is inserted into the VBI.  
2 Alternatively, the streaming content may be served from one source (e.g., primary  
3 content provider 22(1)) while the enhancing content is served from a second  
4 source (e.g., secondary content provider 22(2)).

5 The enhancing content comprises the three elements: announcements,  
6 triggers, and data files. The three elements are sent at different times to different  
7 IP addresses and ports. The data files include both the enhancement files and the  
8 dependency files.

9 Receiver 64 receives the composite stream or the dual streams. Receiver 64  
10 represents one or more receiver types, such as a broadcast receiver, a network  
11 connection, a cable receiver, and so forth. The receiver extracts the streaming  
12 content (e.g., video and audio data) and sends it to one or two types of video  
13 controls 78: a video control, which is used in Web pages that are not hosted in  
14 WebTV for Windows, and an enhancement video control, which is used in Web  
15 pages that are hosted in WebTV for Windows. The video controls reside in an  
16 HTML page 92 that is opened by a browser 72 (or the WebTV for Windows  
17 software) to support the interactive program.

18 As video is received by the video control 78, elements of the enhancement  
19 stream (announcements, triggers, data files) are received at other components of  
20 the client. The enhancement announcements are passed through one or more filters  
21 76, which examine each announcement for a match against a list of programs in  
22 which the user is interested, or against other types of predefined rules of  
23 acceptance. The filter(s) 76 retain the announcements of interest, and discard the  
24 rest.  
25

1 Selected announcements are stored in the TSS database 82, which also  
2 contains program guide information. The announcements are correlated with the  
3 video content shows that can be enhanced. In this manner, the presence of  
4 enhancement data in conjunction with a show listed in the database indicates that  
5 the show is interactive.

6 Enhancement listener 74 handles the announcements stored in the TSS  
7 database 82 when the user requests the corresponding interactive program. The  
8 listener 74 uses information from the announcements to prepare to receive triggers.  
9 The enhancement listener 74 is implemented as an ActiveX control that responds  
10 to enhancement stream events. Like the video controls, the enhancement listener  
11 is hosted in an enhancement page 92 displayed by browser 72.

12 Depending upon the trigger type, the listener 74 may perform several  
13 different functions. A data-type trigger is used in facilitating reception of the data  
14 files. The data-type trigger contains the IP address and port at which the data files  
15 will be delivered. The enhancing data files are temporarily cached in spool  
16 directory 84.

17 A navigation-type trigger is used for navigation about the container HTML  
18 page 92. A script-type trigger contains information to invoke one or more scripts  
19 80 for execution. The scripts use the enhancing data stored in the spook directory  
20 84 to enhancing the streaming content being played by the video control 78.

### 21 **Content Synchronization**

22 Fig. 4 shows exemplary steps in a method for synchronizing streaming  
23 content with enhancing content through use of announcements and triggers. At  
24 step 100, the client receives streaming and enhancing content from one or more  
25

content providers. The receiver passes the streaming content to video control 78 in an HTML page 72 (step 102).

Meanwhile, the enhancement listener 74 executes in the background to listen for announcements that may accompany streaming content. One or more filters 76 register with, and are loaded by, the announcement listener 74 to filter out unwanted announcements received in the enhancing content stream (step 104). At step 106, announcements surviving the filtering process are stored in TSS database 82. The filter 176 calls a loader (e.g., DLL object) to load the announcement in the TSS database. The selected announcements are stored in correlation with the titles or identities of the streaming content programs to indicate that the programs are interactive.

Each time a user tunes a new channel, browser 72 checks the TSS database 82 to see if the new show is interactive (step 108). If not (i.e., the “no” branch from step 108), the client simply plays the streaming content (step 110). On the other hand, if the new show is interactive (i.e., the “yes” branch from step 108) and assuming the user has enhancements enabled, the client browser opens a container HTML page 92 and displays a special icon indicating that the show is interactive (step 112). The container page 92 includes the controls and scripts to render the streaming and enhancing content on the display.

When browser 72 displays an interactive show, the listener 74 listens on the IP address and port specified in an earlier announcement stored in the TSS database 82 (step 114). The announcement listener 74 monitors the IP stream at the address and port for triggers. Triggers are sent at specific times during the associated streaming content to cause an action to occur on a client in relation to

1 the streaming content. In this manner, the enhancing content induced by the  
2 triggers is synchronized with the streaming content.

3 When a trigger is received, the listener 74 processes the trigger (step 116).  
4 Part of the processing determines whether the trigger is a standard trigger, such as  
5 the Broadcast Architecture defined data-type, navigation-type, and script-type  
6 triggers, or a user-defined trigger.

7 For a data-type trigger, the client is prepared to receive enhancing data files  
8 according to a particular protocol (step 118). One example of a data-type trigger,  
9 known as the FTS data trigger, indicates a subdirectory in which to store  
10 enhancing data files in the spool directory 84 and the IP address and port on which  
11 files will be transferred. The FTS data trigger uses a "bpc:" URL syntax to  
12 reference delivered files from HTML. The syntax allows for the use of  
13 subdirectories. A sample FTS data trigger is given as follows:

14  
15 1 <FTS> 233.43.17.17:17817&MyEnhancement  
16

17 The enhancing data files are stored in the MyEnhancement subdirectory of  
18 the spook directory 84 (step 120). The URL to a referenced HTML page in the  
19 MyEnhancement subdirectory is given as follows:

20  
21 bpc://MyEnhancement/funstuff.htm  
22

23 For a navigation-type trigger, the browser uses the trigger information to  
24 perform general navigation operations, such as moving to a top of page or  
25 referencing a target resource (step 122). For a script-type triggers and user-defined



1 triggers, the listener sends an event to the container Web page 92, where they are  
2 handled by scripts 80 embedded in that Web page (step 124).

3 If the triggers involve accessing enhancement data files, the listener 74 uses  
4 the URL to retrieve the data files from the spool directory 84 in timely manner  
5 (step 126). The browser then renders the enhancing content in synchronization  
6 with the streaming content (step 128).

### 7 8 **Trigger-Carried Ticker Information**

9 Another aspect of this invention concerns a way to receive headlines and  
10 other information as triggers and accumulate them into a ticker. Triggers holding  
11 ticker information are accumulated over time and then displayed in a ticker. It also  
12 provides a way to have text fade-in and fade-out (using Dynamic HTML or  
13 “DHTML”).

14 To demonstrate this technology, Fig. 5 shows an HTML page 150 for the  
15 MSNBC Web site “[www.MSNBC.com](http://www.MSNBC.com)” that combines and coordinates both  
16 streaming content and enhancing content. It includes a video pane 152 within  
17 which the streaming video data is played. The MSNBC page 150 also has a static  
18 link 154, such as a link to a home page, weather, or local news. Dynamic links  
19 156 are edited and managed on a more routine basis, such as daily or hourly, and  
20 hence change more often than the static link 154.

21 The MSNBC page also has an advertising space 158 to display DHTML  
22 pages used to present advertisements. A DHTML ticker 160 is provided to scroll  
23 section names, headlines, URLs, schedule information, and so forth.

24 The MSNBC enhancement page 150 operates as follows:  
25

1. The enhancement page 150 is received and rendered by the browser 72.
2. The enhancement page 150 receives triggers containing headlines and other items for the ticker 160 and stores them as elements in an array. The enhancement page 150 also receives triggers for the dynamic links 156.
3. The page operates on a timer to cycle through all of the stored triggers, fading from one headline to the next.
4. Each headline has an associated Web link (URL); if the user clicks on a headline, a child browser window is created in which the referenced page is displayed.

The ticker data is stored in three arrays defined as follows:

```
// MSNBC Headlines
MSNBC_Category = new MakeArray(40);
MSNBC_URL = new MakeArray(40);
MSNBC_Headline = new MakeArray(40);
```

The array “MSNBC\_Category” stores the headline category; “MSNBC\_URL” stores the link associated with the headline, and “MSNBC\_Headline” stores the actual headline text that is displayed in the ticker. Each array can store up to forty elements corresponding to ticker headlines. The array is initially filled with empty strings. As the ticker cycles through the arrays, it ignores any element that is an empty string. To fill out the arrays and thereby add headlines to the ticker data, the content provider transmits a trigger that calls the following Jscript routine:

```

1      function ChangeHeadline(tnum,tcatt,turl,thl)
2      {
3      tnum--;
4      if(tnum >= 0 && tnum < 40)
5      {
6          MSNBC_Category[tnum] = tcatt;
7          MSNBC_URL[tnum] = turl;
8          MSNBC_Headline[tnum] = thl;
9      }
10     }

```

The "ChangeHeadline" function inserts the headline "thl" at the array index "tnum". The value specified in "tnum" allows the content producer to order the headlines in a particular fashion. The ticker cycles through the arrays in numeric order, skipping empty array elements.

Here are some examples of triggers that call "ChangeHeadline". Trigger type 4 causes the trigger listener control 74 on the enhancement page to execute the script specified in the trigger.

```

16      00:00:05.00    trigger 4 (
17      "top.main.ChangeHeadline(1,'Brian','http://msw','T
18      est 1 Headline');" ) only;

```

```

19      00:00:10.00    trigger 4 (
20      "top.main.ChangeHeadline(10,'Seattle','http://msw'
21      , 'Test 10 Headline Test 2 Headline Test 2 Headline
22      Test 2 Headline Test 2 Headline Test 2 Headline
23      Test 2 Headline Test 2 Headline Test 2
24      Headline');" ) only;

```

```

25      00:00:15.00    trigger 4 (
26      "top.main.ChangeHeadline(11,'Seattle','http://msw'
27      , 'Test 11 Headline Test 2 Headline Test 2 Headline
28      Test 2 Headline Test 2 Headline Test 2 Headline
29      Test 2 Headline Test 2 Headline Test 2 Headline
30      Headline');" ) only;

```

Test 2 Headline Test 2 Headline Test 2  
Headline');" ) only;

The following trigger will remove the headline from the array at index 11.

00:00:15.00 trigger 4 (  
"top.main.ChangeHeadline(11,'','','');" ) only;

The following is an excerpt from an actual stream file as generated by the  
MSNBC tools:



steps described. Rather, the specific features and steps are disclosed as exemplary forms of implementing the claimed invention.

1 **CLAIMS**

2 1. A method for synchronizing streaming content with enhancing  
3 content comprising the following steps:

4 receiving an announcement containing information specifying how and  
5 when to receive upcoming enhancing content, the announcement being sent at a  
6 time prior to sending the enhancing content, the enhancing content being  
7 associated with the streaming content;

8 receiving the streaming content;

9 receiving the enhancing content according to the information contained in  
10 the announcement and at a time in synchronization with the streaming content; and  
11 enhancing the streaming content with the enhancing content.

12  
13 2. A method as recited in claim 1, wherein the announcement contains  
14 parameters selected from a group comprising: a broadcast locator, a time when the  
15 corresponding enhancing content is to be sent, a protocol, an identity of the  
16 streaming content that the enhancing content enhances, and a page that contains a  
17 starting point for the enhancing content.

18  
19 3. A method as recited in claim 1, wherein the enhancing content  
20 comprises triggers and data files, the method further comprising the following  
21 steps:

22 receiving the data files; and

23 receiving the triggers at times in synchronization with the streaming  
24 content, the triggers causing operations involving the data files in order to timely  
25 introduce the enhancing content with the streaming content.

1  
2           4.    A method as recited in claim 3, wherein the enhancing content further  
3 comprises dependency files that contain instructions to present content contained  
4 in the data files, the method further comprising the step of delivering the data files  
5 together with the dependency files in a cabinet (CAB) file format.

6  
7           5.    A method as recited in claim 1, wherein the receiving steps comprise  
8 the step of receiving the streaming content and the enhancing content in a  
9 composite stream of one source.

10  
11           6.    A method as recited in claim 1, wherein the receiving steps comprise  
12 the following steps:

13               receiving the streaming content from a first source; and

14               receiving the enhancing content from a second source different from the  
15 first source.

16  
17           7.    A method as recited in claim 1, further comprising the step of  
18 displaying the enhancing content as a ticker.

19  
20           8.    A computer-readable medium having computer-executable  
21 instructions for performing the steps of the method as recited in claim 1.



1           9. A method for synchronizing streaming content with enhancing  
2 content comprising the following steps:

3           forming announcements containing information specifying a first address  
4 and a time at which to receive upcoming triggers;

5           sending the announcements to a second address;

6           monitoring the second address to receive the announcements;

7           filtering the announcements to retain selected announcements;

8           monitoring the first address at the time specified in the selected  
9 announcements to receive the triggers; and

10          processing the triggers to coordinate presentation of the enhancing content  
11 with the streaming content.

12  
13          10. A method as recited in claim 9, wherein the forming step comprises  
14 the step of creating an announcement to contain parameters selected from a group  
15 comprising: a broadcast locator, a time when a corresponding trigger is to be  
16 broadcast, a broadcast protocol, an identity of the streaming content that the  
17 enhancing content enhances, and a page that contains a starting point for the  
18 enhancing content.

19  
20          11. A method as recited in claim 9, wherein the processing step  
21 comprises the step of receiving the enhancing content according to a  
22 predetermined protocol and storing the enhancing content.

1           **12.**    A method as recited in claim 9, wherein the processing step  
2 comprises the step of navigating within a container HTML page.

3  
4           **13.**    A method as recited in claim 9, wherein the processing step  
5 comprises the step of invoking a script within a container HTML page.

6  
7           **14.**    A method as recited in claim 9, further comprising the step of  
8 sending the enhancing content together with the triggers.

9  
10          **15.**    A method as recited in claim 9, further comprising the step of  
11 delivering the streaming content, the enhancing content, and the triggers from a  
12 same source.

13  
14          **16.**    A method as recited in claim 9, further comprising the following  
15 steps:

16           delivering the enhancing content from a first source; and

17           delivering the streaming content and the triggers from a second source  
18 different from the first source.

19  
20          **17.**    A method as recited in claim 9, further comprising the step of  
21 displaying the enhancing content together with the streaming content.

22  
23          **18.**    A method as recited in claim 9, wherein the enhancing content  
24 comprises a ticker, and further comprising the following steps:

25           delivering triggers that contain items for the ticker;

1 displaying the ticker together with the streaming content; and  
2 presenting the items from the triggers within the ticker.  
3

4 **19.** Computer-readable media distributed at a content provider and a  
5 client and having computer-executable instructions for performing the steps of the  
6 method as recited in claim 9.  
7

8 **20.** A method comprising the following steps:  
9 displaying streaming content;  
10 monitoring an announcement address to receive announcements pertaining  
11 to enhancing content for enhancing the streaming content, the announcements  
12 containing information that specify a trigger address and times at which to receive  
13 upcoming triggers;  
14 filtering the announcements to retain selected announcements;  
15 storing the selected announcements;  
16 monitoring the trigger address at the times specified in the selected  
17 announcements to receive corresponding triggers; and  
18 processing the triggers to cause one of the following events to occur: (1)  
19 receive one or more data files having the enhancing content, or (2) utilize the  
20 enhancing content in the data files to enhance the streaming content.  
21

22 **21.** A method as recited in claim 20, further comprising the step of  
23 caching the data files.  
24  
25

1           **22.**    A method as recited in claim 20, further comprising the step of  
2 presenting the streaming content and the enhancing content using an HTML page.

3  
4           **23.**    A method as recited in claim 20, further comprising the following  
5 steps:

6           using information from the trigger to invoke a script; and  
7           executing the script to enhance the streaming content.

8  
9           **24.**    A method as recited in claim 20, further comprising the following  
10 steps:

11           receiving triggers that contain items for a ticker;  
12           displaying the ticker together with the streaming content; and  
13           presenting the items from the triggers within the ticker.

14  
15           **25.**    A computer-readable medium having computer-executable  
16 instructions for performing the steps of the method as recited in claim 20.

17  
18           **26.**    A method comprising the following steps:  
19           monitoring an IP (Internet Protocol) address to receive triggers, each trigger  
20 containing at least one item for a ticker;  
21           forming an array of the items received in the triggers; and  
22           displaying the array within the ticker.

1           **27.**    A method as recited in claim 26, further comprising the step of  
2 receiving announcements at another IP address, the announcements being used to  
3 announce upcoming transmissions of the triggers.

4  
5           **28.**    A computer-readable system having computer-executable  
6 instructions for performing the following steps:

7           monitoring an announcement address to receive announcements pertaining  
8 to enhancing content for enhancing the streaming content, the announcements  
9 containing information that specify a trigger address and a time at which to receive  
10 upcoming triggers;

11           filtering the announcements to retain selected announcements;

12           monitoring the trigger IP address at the time specified in one of the selected  
13 announcements to receive a corresponding trigger; and

14           processing the trigger to cause utilization of the enhancing content to  
15 enhance the streaming content.

16  
17           **29.**    A computer-readable system having computer-executable  
18 instructions for performing the following steps:

19           monitoring an IP address to receive triggers, each trigger containing at least  
20 one item; and

21           presenting a ticker that contains the items.

22  
23           **30.**    A system for synchronizing streaming content with enhancing  
24 content, comprising:

25           at least one content server;

1 a client;

2 the content server being configured to form announcements that contain  
3 information specifying an IP address and a time at which to receive upcoming  
4 triggers, the content server sending the announcements to the client; and

5 the client being configured to receive the announcements and monitor the  
6 IP address at the time specified in the announcements to receive the triggers, the  
7 client processing the triggers to coordinate presentation of the enhancing content  
8 with the streaming content.

9  
10 **31.** A system as recited in claim 30, wherein the announcements contain  
11 parameters selected from a group comprising: a broadcast locator, a time when a  
12 corresponding trigger is to be broadcast, a broadcast protocol, an identity of the  
13 streaming content that the enhancing content enhances, and a page that contains a  
14 starting point for the enhancing content.

15  
16 **32.** A system as recited in claim 30, wherein the client receives the  
17 enhancing content according to a predetermined protocol and caches the enhancing  
18 content.

19  
20 **33.** A system as recited in claim 30, wherein the client uses information  
21 from the trigger to navigate within a container HTML page.

22  
23 **34.** A system as recited in claim 30, wherein the client uses information  
24 from the trigger to invoke a script within a container HTML page.

1           **35.**     A system as recited in claim 30, wherein the content server delivers  
2 the streaming content, the enhancing content, and the triggers.

3  
4           **36.**     A system as recited in claim 30, wherein the content server delivers  
5 the enhancing content and the triggers, and further comprising a second content  
6 server to deliver the streaming content.

7  
8           **37.**     A system as recited in claim 30, wherein the triggers contain items  
9 for a ticker and the client displays the ticker together with the streaming content.

10  
11           **38.**     A client software architecture, comprising:  
12           a video control to play video content;  
13           a listener to monitor an announcement IP (Internet Protocol) address to  
14 receive announcements pertaining to enhancing content for enhancing the video  
15 content, the announcements containing information that specify a trigger IP  
16 address and times at which to receive upcoming triggers;  
17           the listener further monitoring the trigger IP address at the times specified  
18 by the announcements to receive corresponding triggers; and  
19           a rendering component to present the video content and to enhance the  
20 video content with the enhancing content according to instructions received in the  
21 triggers.

1       **39.** A client software architecture as recited in claim 38, further  
2 comprising a storage to hold the announcements in correlation with an identity of  
3 the video content.

4  
5       **40.** A client software architecture as recited in claim 38, further  
6 comprising a cache to hold the enhancing content.

7  
8       **41.** A client software architecture as recited in claim 38, wherein the  
9 listener and video control are contained within an HTML page rendered by the  
10 rendering component.


11  
12       **42.** A client software architecture as recited in claim 41, wherein the  
13 HTML page also has one or more scripts to process the instructions contained in  
14 the triggers.


15  
16       **43.** A client software architecture, comprising:  
17 a first code segment for monitoring a broadcast or multicast IP address to  
18 receive triggers, each trigger containing at least one item for a ticker; and  
19 a second code segment for rendering the ticker with the items received via  
20 the triggers.




## ABSTRACT

A client-server architecture synchronizes streaming content with enhancing content via pre-announced triggers. The architecture includes server-based components to generate announcements containing information specifying how and when to receive upcoming triggers that will be transmitted at a later time. The server transmits the announcements to a general broadcast or multicast IP address. Client-based components monitor the IP address to receive and filter the announcements. Selected announcements are stored in a guide database in correlation with the streaming content programs to indicate that the programs are interactive. When a user tunes to an interactive program, the client opens a container HTML page that contains controls to receive the streaming content program and to extract the announcements from the guide database. The latter control monitors the IP address at the times specified in the selected announcements to receive the triggers corresponding to the interactive program. The server delivers the triggers at times synchronized to the streaming content. When triggers arrive, the client control processes the triggers to coordinate presentation of the enhancing content with the streaming content program. The triggers may further be used to carry items that fill a ticker being displayed with the program.

*Fig. 1*

*Fig. 2*

*Fig. 3*





Fig. 4

*Fig. 5*

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

Inventorship .....Feinleib et al.  
 Applicant ..... Microsoft Corporation  
 Attorney's Docket No. .... MSI-288US  
 Title: System and Method for Synchronizing Streaming Content with Enhancing  
 Content Using Pre-announced Triggers

**DECLARATION FOR PATENT APPLICATION**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled "System and Method for Synchronizing Streaming Content with Enhancing Content Using Pre-announced Triggers," the specification of which is attached hereto.

I have reviewed and understand the content of the above-identified specification, including the claims.

I acknowledge the duty to disclose information which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, § 1.56(a).

PRIOR FOREIGN APPLICATIONS: no applications for foreign patents or inventor's certificates have been filed prior to the date of execution of this declaration.

**Power of Attorney**

I appoint the following attorneys to prosecute this application and transact all future business in the Patent and Trademark Office connected with this application:

Lewis C. Lee, Reg. No. 34,656; Daniel L. Hayes, Reg. No. 34,618; Allan T. Sponseller, Reg. 38,318, Steven R. Sponseller, Reg. No. 39,384, James R. Banowsky, Reg. No. 37,773, David A. Morasch, Reg. No. 42,905 Katie E. Sako, Reg. No. 32,628 and Daniel D. Crouse, Reg. No. 32,022.

Send correspondence to: LEE & HAYES, PLLC, W. 201 North River Drive, Suite 430, Spokane, Washington, 99201. Direct telephone calls to: Lewis C. Lee (509) 324-9256.


All statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statement may jeopardize the validity of the application or any patent issued therefrom.

\*\*\*\*\*

Full name of inventor:

David Feinleib

Inventor's Signature



Date:

3/29/99

Residence:

Kirkland, WA

Citizenship:

USA

Post Office Address:

6756 Lake Washington Blvd. NE #D34  
Kirkland, WA 98033




\*\*\*\*\*

Full name of inventor:

Isaac A. Sheldon

Inventor's Signature



Date: Mar 29, 1999

Residence:

Seattle, WA

Citizenship:

USA

Post Office Address:

3012 NE 97th Street  
Seattle, WA 98115

66760"5828260